



## INDUSTIRAL TYPE

### SPECIFICATION

#### HOUSING

- DIE-FORMED COLD-ROLLED STEEL  
AVAILABLE IN  0.4,  0.6,  0.8 mm.  
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER  
FABRICATION TO PREVENT ANY CORROSION  
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER  
POWDER COATING
- G5 ROTARY LOCKED LAMP HOLDER
- THW  0.5 sqmm./105c  1.0 sqmm./70c  
WIRING CABLE

#### REFLECTOR

- 99.80% PURITY ANODIZED ALUMINIUM  
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF  
 TR 87%  TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE  
OPTIMUM OPTICAL PERFORMANCE FOR LONGITUDINAL

#### OPTION REFLECTOR

- WHITE STOVE ENAMEL STEEL SHEEL (WIS)

#### INSTALLATION

- SURFACE OR SUSPENDED MOUNTING

### DIMENSIONS (mm.)

MODEL	TYPE	W	L	H
WIA2/1S	T5	130	570	60
WIA2/1L	T5	130	1170	60
WIS2/1S	T5	130	570	60
WIS2/1L	T5	130	1170	60

