



PROFILE LOUVER TYPE

SPECIFICATION

HOUSING

- DIE-FORMED COLD-ROLLED STEEL
AVAILABLE IN □ 0.4, □ 0.6, □ 0.8 mm.
STEEL THICKNESS
- ALL METAL PART ARE RUST-PROOFED AFTER
FABRICATION TO PREVENT ANY CORROSION
(ZINE PHOSPHATE)
- FINISHED WITH HIGH GRADE EPOXY POLYESTER
POWDER COATING
- G5 ROTARY LOCKED LAMP HOLDER
- THW □ 0.5 sqmm./105c □ 1.0 sqmm./70c
WIRING CABLE

REFLECTOR & LOUVER

- 99.80% PURITY ANODIZED ALUMINIUM
REFLECTOR TO PROVIDE TOTAL REFLECTANCE OF
□ TR 87% □ TR 95% FOR MIRROR FINISH
- PARABOLIC REFLECTOR MACHINED TO PROVIDE
OPTIMUM OPTICAL PERFORMANCE FOR
LONGITUDINAL
- CHRISTMAS TREE PROFILES FOR TRANSVERSAL

INSTALLATION

- AVAILABLE IN RECESSED T-BAR OR CONCEAL CEILING

DIMENSIONS (mm.)

MODEL	TYPE	W	W1	L	L1	H	CEILING CUT OUT (mm.) A x B
WLR1/6/2S	T5	595	557	570	595	80	570 x 575
WLR1/6/3S	T5	595	557	570	595	80	570 x 575
WLR1/6/4S	T5	595	557	570	595	80	570 x 575
WLR1/6/2L	T5	595	557	1173	1197	80	570 x 1178
WLR1/6/3L	T5	595	557	1173	1197	80	570 x 1178
WLR1/6/4L	T5	595	557	1173	1197	80	570 x 1178

